

# **AV1310            1.3 Megapixel Color Camera**

# **AV1310DN       1.3 Megapixel Day/Night Camera**

## ***Bid-pec*** \_\_\_\_\_

### **1.0 Description**

The AV1310 compact series camera is an MJPEG encoding, 1.3 Megapixel resolution, IP addressable camera, designed to deliver full motion high definition progressive scan digital video across local area networks in a compact package. The AV1310 is a high sensitivity, PoE (IEEE 802.3af) compliant camera with color and Day/Night configurations. Built with Arecont Vision's proprietary massively-parallel MegaVideo® technology, the AV1310 has the ability to output multiple image formats allowing the simultaneous viewing of the full resolution field of view and regions of interest for high definition forensic zooming. This camera offers over four times the resolution of standard resolution IP cameras with the ability to output full real time frame rates.

### **2.0 Bid Specification**

- The camera shall be 1.3 megapixels utilizing a 1/2" CMOS sensor.
- The camera shall support MJPEG encoding format.
- The camera shall output at a maximum resolution of 1280(H) x 1024(V) pixels at a maximum frame rate up to 32 frames per second (FPS).
- It shall be possible to program the camera to output a variety of lower resolution images, i.e. 1280(H) x 720(V) pixels.
- The camera shall feature streaming of the full field of view (FOV) and simultaneous multiple regions of interest (ROI) for forensic zooming.
- The camera shall be equipped with a 100 Mbps LAN connector and can deliver image data at a maximum data rate of up to 55 Megabits per second (55 Mbps).
- The camera shall use a wide variety of C/CS mount 1/2" lenses. (Note that some CS lenses and all C-mount lenses may require an adaptor ring. Megapixel quality lenses are the preferred choice for our entire camera line.)
- The camera shall provide 21 levels of compression quality for optimal viewing and archiving.
- The camera shall support a minimum TFTP and HTTP network protocols.
- The cameras shall feature precision motion detection with a minimum of 64 detection zones.
- The camera shall feature automatic exposure, automatic multi-matrix white balance, shutter speed control, 50/60Hz selectable flicker control, programmable brightness, saturation, gamma, sharpness, windowing and decimation, simultaneous delivery of full-field view and zoomed images at video frame rate, instantaneous electronic zoom, pan and tilt, and electronic image rotation by 180 degrees.
- The camera shall incorporate necessary algorithms and circuits to detect motion in low light with clarity.
- The camera shall support a minimum illumination of 0.1 Lux @ F1.4 in color mode.
- The camera shall support an IR sensitive minimum illumination of 0 Lux in B/W mode (DN version only).
- The camera's primary power source shall be Power over Ethernet (PoE) complying with the IEEE 802.3af standard.
- This camera shall feature a durable aluminum housing that minimizes fire hazards. Camera should be mounted using a 1/4" x 20 threaded hole at the bottom of the housing.
- The camera shall be utilized for indoor use but can be used in outdoor applications with an appropriate enclosure.
- The camera's operating ambient temperature is 0°C (32°F) to 50°C (122°F).

- The camera shall be FCC Part 15, Class A, CE and RoHS compliant
- The camera shall have dimensions of: 3" (76mm) W x 2.5" (63.5mm) H x 1.25" (31.7mm) D weighing 5.8oz (164g) without lens.

## Quick-Spec

---

### 3.0 Minimum Performance Specification

Megapixel camera must meet the following operating requirements

#### Operational

Imaging	1.3 megapixel CMOS image sensor 1/2" optical format Bayer mosaic RGB filter
Active Pixel Count	1280(H) x 1024(V) pixel array
Minimum illumination	Color: 0.1 Lux @ F1.4 Day/Night: 0 Lux, IR sensitive
Dynamic range	61 dB
Maximum SNR	50 dB

#### Full Field of View (FOV) Resolutions

1280x1024 (HxW) 1.3 megapixel  
640x512 (HxW) 1/4 resolution

#### Cropped Field of View Resolutions

1280x720 HDTV - 720p  
1024x768 XGA  
800x600 SVGA  
704x570 PAL  
704x480 NTSC  
640x480 VGA  
352x288 CIF  
320x240 SIF

#### Data Transmission

Data rate up to 55Mbps  
Video frame rate up to  
32fps @ 1280x1024  
Motion JPEG with 21 levels of quality  
TFTP and HTTP image transmission protocols  
100 Base-T Ethernet Network Interface  
Multi-streaming: 8 non-identical streams

#### Programmability

Auto Exposure (AE) and Gain Control (AGC) >120dB  
On-camera real-time motion detection with 64 detection zones  
Auto backlight compensation  
Auto multi-matrix white balance  
50/60Hz selectable flicker control  
Electronic pan, tilt, zoom (PTZ)  
Electronic image flip - 180 degree rotation  
Resolution windowing down to 32x32 pixels window  
Programmable shutter speeds to minimize motion blur  
MoonLight™ mode - extended exposure and proprietary noise cancellation  
Programmable resolution, brightness, saturation, gamma, sharpness, tint

Picture-in-Picture: simultaneous delivery of full field of view and zoomed images  
Bandwidth & storage savings by running at 1/4 resolution

**Electrical**

General purpose opto-coupled input and output  
Power over Ethernet (PoE): PoE 802.3af  
Power consumption 3 Watts maximum

**Mechanical**

Dimensions(H x W x D).....3"W (76 mm) x 2.5"H (63.5 mm) x 1.25"D (31.7mm) (w/o lens)  
Weight.....8.6 oz (243 grams) (w/o lens)  
Lens.....C/CS lens mount

**Environmental**

Operating temperature 0°C (32 °F) to +50°C (122 °F)  
Storage temperature -20°C (-4 °F) to +60°C (140 °F)  
Humidity 0% to 90% (non condensing)

**Regulatory**

FCC, Class A  
CE and RoHS compliant

**Related Documentation**

1. AV User Manual
2. AV Software Developer Kit Manual
3. AV1310, AV2110, AV3110, AV5110 Network Camera Specification

**4.0 Model Numbers**

The camera shall be Arecont Vision model AV1310, 1.3 megapixel color camera  
The camera shall be Arecont Vision model AV1310DN, 1.3 megapixel day/night camera

**5.0 Warranty**

Minimum 1 Year parts and labor

*Arecont Vision reserves the right to change products or specifications without notice.*